

O*NET 6.0 Database
Data Dictionary
Visual FoxPro Version



ALMIS Resource Center

<http://www.almisdb.org/>

and

National Crosswalk Service Center
Iowa Center for Career and Occupational Resources
Department of Education
Grimes State Office Building
Des Moines, Iowa 50319

<http://www.xwalkcenter.org/onet60/index.html>

Telephone 515-242-5034

Data Dictionary O*NET 6.0 Database Visual FoxPro Version

Introduction

O*NET, the Occupational Information Network, is a comprehensive database of worker attributes and job characteristics. As the replacement for the Dictionary of Occupational Titles (DOT), O*NET will be the nation's primary source of occupational information.

Information from the O*NET Database is available from the National O*NET Consortium (<http://www.onetcenter.org/>). The consortium utilizes two means of delivery: an on-line database viewer (<http://online.onetcenter.org/>) and a downloadable database consisting of a series of tab-delimited text files, along with related file documentation (<http://www.onetcenter.org/database.html>).

The National Crosswalk Service Center (NCSC), formerly the NOICC Crosswalk and Data Center, has distributed resources related to occupational classifications such as the DOT since 1983. The contents of the files described in this document were taken from the database downloaded from the third Internet page cited above. The tables are also available in a tab-delimited text, MS Access and SAS/PC formats. This document describes the format of the Visual FoxPro database. File layouts for the other versions differ. Contact the NCSC for more information.

The contents of the files in the database described in this document were adapted from the files downloaded from the consortium web site. Some fields were eliminated from these tables to eliminate redundancy and bring the database into a more normalized configuration.

Database Changes

The July 2004 release of the O*NET 6.0 database was a development version. In December 2004 that version moved into production, used in the O*NET Online application.

The O*NET 6.0 database is the second to include new data from the O*NET Data Collection Program and brings to 180 the number of occupations with information collected through that program. Highlights include:

- New and revised **Task Statements** for 140 O*NET-SOC occupations
- Addition of **Task Statement ratings** (importance and frequency) for 126 O*NET-SOC occupations
- Updated **Abilities, Work Activities, Knowledge, Skills, and Work Context** data for 126 occupations
- Additional **Work Context** data for 126 occupations
- Addition of **Training and Work Experience** and **Education** data for 126 occupations
- Addition of **Work Styles** data for 126 occupations

With the introduction of information from the data collection program in version 5.0 of the database, the O*NET database no longer contains a homogeneous set of variables and measures for all occupations. The O*NET Center continues to make version 4.0 of the database available on their web site. That is the last version made up entirely of analyst data, with a uniform set of descriptors. The NCSC continues to make the Visual FoxPro, SAS/PC and MS Access versions available at <http://www.xwalkcenter.org/onet40/index.html>.

HOW TO READ A TABLE DEFINITION

Each table definition contains complete information about the structure of a table. Each definition includes: the name of the table, a complete list of each column name and data type, complete constraint information, and short descriptions of the columns. The following illustration identifies each component of a table definition.

Interest -- Interest Descriptors and their ratings for each occupation

Column	Type	Constraint	Description
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
Scalid	char(2)	Primary Key 3	Unique code for O*NET descriptors scale
datavalue	number(6,2)		Value of descriptor rating
Constraint Information			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid			
Other Information			
<ul style="list-style-type: none"> ◆ 8,100 Records ◆ Source table: interest 			

Constraint: Specifies whether this column is part of the Primary Key or participates in one or more Foreign Keys. Numbers in this column refer to Foreign Keys where more detailed information can be found in the **Constraints Information** section.

Other Information: Provides count of the number of records in the table and the table(s) in the source O*NET database from which the contents were derived.

Constraint Information: Provides complete information on each Foreign Key used in the table. Each note indicates which table and columns are being referenced.

Short description of the data intended for this column.

TABLE CONSTRAINTS

The Constraint section of each table definition identifies all Primary Keys and Foreign Keys for the table. The constraints for a table specify rules for data that will be stored in that table. These rules exist in the form of either Primary Keys or Foreign Keys. The definitions of these terms appear below:

Primary Key: The *Primary Key* is a column or group of columns that shall always be (1) non-null and (2) unique. Only one primary key exists for each table. A Primary Key constraint is enforced on a table so that each row in the table can be uniquely identified.

Foreign Key: A *Foreign Key* is a column or group of columns where each value or group of values exists as a Primary Key in another table. Foreign Key constraints are used so that data for a column or group of columns can be validated against another table containing a list of valid values for that column or group of columns.

O*NET 6.0 Data Dictionary – Core Table Formats

Descriptive Tables: These tables contain information describing the classifications and variables found in the O*NET 6.0 database.

onetcode -- This table contains one record for each O*NET-SOC Occupation			
Column	Type	Constraint	Description
onetcode	char(8)	Primary Key	Unique occupation code based on SOC code, modified for O*NET
onetttitle	char(105)		Occupation title
onetdesc	memo		Description of occupation
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> ◆ 1,167 Records ◆ O*NET source tables: onetsoc_data 			

Contmodl -- O*NET content model reference			
Column	Type	Constraint	Description
elementid	char(15)	Primary Key	Unique code for ratings Scale
elemntname	char(140)		Descriptor Name
dlemntdesc	memo		Description of Descriptor
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> ◆ 564 Records ◆ Source table: onet_content_model_reference 			

scaleref – Provides a reference to the scale names and values			
Column	Type	Constraint	Description
scaleid	char(3)	Primary Key	Unique code for ratings Scale
scalename	char(50)		Name of Scale
scalemmin	Number(3,0)		Minimum value the descriptor scale can take
scalemmax	Number(3,0)		Maximum value the descriptor scale can take
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> ◆ 69 Records ◆ Source table: scales_reference 			

Jobzone -- This table contains descriptions of each of O*NET's job zones			
Column	Type	Constraint	Description
jobzonecd	char(1)	Primary Key	Unique code for Job Zone
jobzone	char(50)		Name of Job Zone
experience	Memo		Experience required to be considered part of this job zone
education	Memo		Education required to be considered part of this job zone
training	Memo		Training required to be considered part of this job zone
examples	Memo		Examples of the types of jobs in this job zone
svprange	char(15)		
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> ◆ 5 Records ◆ Source table: job_zone_reference 			

domsourc -- This table contains one record for data source			
Column	Type	Constraint	Description
sourccode	char(1)	Primary Key	Unique code for each source
domsourc	char(30)		Source description
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> ◆ 4 Records ◆ O*NET source tables: None (created by NCSC) 			

Data tables: These tables contain the variables which define the characteristics of O*NET occupations.

ability -- Ability Descriptors and their ratings for each occupation			
Column	Type	Constraint	Description
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	char(3)	Primary Key 3	Unique code for O*NET descriptors scale
datavalue	number(6,2)		Value of descriptor rating
N	number(4)		Sample size
Stderr	number(6,2)		Standard error
lowerci	number(6,2)		Lower 95% confidence interval bound
upperci	number(6,2)		Upper 95% confidence interval bound
supflag	char(3)		Suppression recommended (low precision indicator – Y=Yes, N=No)
Notrel	char(3)		Not relevant for the occupation (Y=Yes, N=No)
Date	char(7)		Date when data were updated (MM/YYYY)
sourccode	char(1)	4	Code for source of the data
Constraint Information			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid 4 Foreign Key references: comsourc.sourccode			
Other Information			
◆ 94,432 Records ◆ Source table: ability			

educ – Mapping of O*NET codes to education, training and experience ratings			
Column	Type	Constraint	Description
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	char(3)	Primary Key 3	Unique code for O*NET descriptors scale
category	number(5)	Primary Key	Percent frequency category (refer to bookloc table)
datavalue	number(6,2)		Value of descriptor rating
n	number(4)		Sample size
stderr	number(6,2)		Standard error
lowerci	number(6,2)		Lower 95% confidence interval bound
upperci	number(6,2)		Upper 95% confidence interval bound
supflag	char(3)		Suppression recommended (low precision indicator – Y=Yes, N=No)
date	char(7)		Date when data were updated (MM/YYYY)
sourccode	char(1)	4	Code for source of the data
Constraint Information			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid 4 Foreign Key references: comsourc.sourccode			
Other Information			
◆ 7,380 Records ◆ Source table: EducTrainExp			

interest – Interest Descriptors and their ratings for each occupation			
Column	Type	Constraint	Description
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	char(3)	Primary Key 3	Unique code for O*NET descriptors scale
datavalue	number(6,2)		Value of descriptor rating
date	char(7)		Date when data were updated (MM/YYYY)
sourccode	char(1)	4	Code for source of the data
Constraint Information			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid 4 Foreign Key references: comsourc.sourccode			
Other Information			
<ul style="list-style-type: none"> ◆ 8,100 Records ◆ Source table: interest 			

knowledg – Knowledge Descriptors and their ratings for each occupation			
Column	Type	Constraint	Description
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	char(3)	Primary Key 3	Unique code for O*NET descriptors scale
datavalue	number(6,2)		Value of descriptor rating
n	number(4)		Sample size
stderr	number(6,2)		Standard error
lowerci	number(6,2)		Lower 95% confidence interval bound
upperci	number(6,2)		Upper 95% confidence interval bound
supflag	char(3)		Suppression recommended (low precision indicator – Y=Yes, N=No)
notrel	char(3)		Not relevant for the occupation (Y=Yes, N=No)
date	char(7)		Date when data were updated (MM/YYYY)
sourccode	char(1)	4	Code for source of the data
Constraint Information			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid 4 Foreign Key references: comsourc.sourccode			
Other Information			
<ul style="list-style-type: none"> ◆ 59,928 Records ◆ Source table: knowledge 			

onetzone -- This table contains the Job Zone value for each O*NET-SOC Occupation			
Column	Type	Constraint	Description
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
jobzonecd	char(1)	2	Job Zone of the O*NET-SOC occupation
Date	char(7)		Date when data were updated (MM/YYYY)
sourcecode	char(1)	3	Code for source of the data
Constraint Information			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: jobzone.jobzonecd 3 Foreign Key references: comsourc.sourcecode			
Other Information			
◆ 908 Records ◆ O*NET source tables: onetsoc_job_zones			

skills -- Skills Descriptors and their ratings for each occupation			
Column	Type	Constraint	Description
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	char(3)	Primary Key 3	Unique code for O*NET descriptors scale
datavalue	number(6,2)		Value of descriptor rating
n	number(4)		Sample size
stderr	number(6,2)		Standard error
lowerci	number(6,2)		Lower 95% confidence interval bound
upperci	number(6,2)		Upper 95% confidence interval bound
supflag	char(3)		Suppression recommended (low precision indicator – Y=Yes, N=No)
notrel	char(3)		Not relevant for the occupation (Y=Yes, N=No)
date	char(7)		Date when data were updated (MM/YYYY)
sourcecode	char(1)	4	Code for source of the data
Constraint Information			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid 4 Foreign Key references: comsourc.sourcecode			
Other Information			
◆ 63,560 Records ◆ Source table: skills			

activity -- Work Activity Descriptors and their ratings for each occupation			
Column	Type	Constraint	Description
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	char(3)	Primary Key 3	Unique code for O*NET descriptors scale
datavalue	number(6,2)		Value of descriptor rating
n	number(4)		Sample size
stderr	number(6,2)		Standard error
lowerci	number(6,2)		Lower 95% confidence interval bound
upperci	number(6,2)		Upper 95% confidence interval bound
supflag	char(3)		Suppression recommended (low precision indicator – Y=Yes, N=No)
notrel	char(3)		Not relevant for the occupation (Y=Yes, N=No)
date	char(7)		Date when data were updated (MM/YYYY)
sourccode	char(1)	4	Code for source of the data
Constraint Information			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid 4 Foreign Key references: comsourc.sourccode			
Other Information			
◆ 74,456 Records ◆ Source table: WorkActivity			

context -- Work Context Descriptors and their ratings for each occupation			
Column	Type	Constraint	Description
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	char(3)	Primary Key 3	Unique code for O*NET descriptors scale
Category	char(1)	Primary Key	Percent frequency category (refer to bookloc table)
Datavalue	number(6,2)		Value of descriptor rating
N	number(4)		Sample size
Stderr	number(6,2)		Standard error
Lowerci	number(6,2)		Lower 95% confidence interval bound
Upperci	number(6,2)		Upper 95% confidence interval bound
Supflag	char(3)		Suppression recommended (low precision indicator – Y=Yes, N=No)
Notrel	char(3)		Not relevant for the occupation (Y=Yes, N=No)
Date	char(7)		Date when data were updated (MM/YYYY)
Sourccode	char(1)	4	Code for source of the data
Constraint Information			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid 4 Foreign Key references: comsourc.sourccode			
Other Information			
◆ 88,504 Records ◆ Source table: WorkContext			

styles -- Work Styles Descriptors and their ratings for each occupation			
Column	Type	Constraint	Description
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	char(3)	Primary Key 3	Unique code for O*NET descriptors scale
datavalue	number(6,2)		Value of descriptor rating
n	number(4)		Sample size
stderr	number(6,2)		Standard error
lowerci	number(6,2)		Lower 95% confidence interval bound
upperci	number(6,2)		Upper 95% confidence interval bound
supflag	char(3)		Suppression recommended (low precision indicator – Y=Yes, N=No)
date	char(7)		Date when data were updated (MM/YYYY)
sourccode	char(1)	4	Code for source of the data
Constraint Information			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid 4 Foreign Key references: comsourc.sourccode			
Other Information			
◆ 2,880 Records ◆ Source table: WorkStyles			

workvalu -- Work Value Descriptors and their ratings for each occupation			
Column	Type	Constraint	Description
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	char(3)	Primary Key 3	Unique code for O*NET descriptors scale
datavalue	number(6,2)		Value of descriptor rating
Date	char(7)		Date when data were updated (MM/YYYY)
sourccode	char(1)	4	Code for source of the data
Constraint Information			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid 4 Foreign Key references: comsourc.sourccode			
Other Information			
◆ 24,300 Records ◆ Source table: WorkValue			

tasks -- Provides each O*NET-SOC code (occupation) mapping to several tasks associated with the occupation NOTE: This table did not have a unique field as received from O*NET. The table was restructured to include a unique Primary Key by the addition of the Task Number field.			
Column	Type	Constraint	Description
onetcode	char(8)	Primary Key 1	Unique ONET-SOC Code
tasknumber	char(3)	Primary Key	Line number of each task within ONET-SOC Code
taskid	number(8,0)		Identifies each task containing data ratings
Task	Memo		Tasks involved in occupation
tasktype	char(12)		Core or supplemental
incumb	number(4,0)		Number of incumbents providing task information
scaleid	char(3)		Scale used as the basis for the rating
datavalue	number(6,2)		Rating associated with each task of O*NET occupation
N	number(4,0)		Sample size
stderr	number(6,2)		Standard error
lowerci	number(6,2)		Lower 95% Confidence Interval Bound
upperci	number(6,2)		Upper 95% Confidence Interval Bound
supflag	char(3)		Low precision indicator (Y=yes, N=no)
pctrel	number(6,2)		Relevance of each task to the O*NET occupation
Nr	number(4,0)		Sample size
rstder	number(6,2)		Standard error
lower	number(6,2)		Lower 95% Confidence Interval Bound
uupper	number(6,2)		Upper 95% Confidence Interval Bound
rsupflag	char(3)		Low precision indicator (Y=yes, N=no)
f1pct	number(6,2)		Yearly or less: percent frequency category rating for each task of O*NET occupation
nf1	number(4,0)		Sample size
f1stderr	number(6,2)		Standard error
f1lower	number(6,2)		Lower 95% Confidence Interval Bound
f1upper	number(6,2)		Upper 95% Confidence Interval Bound
f1supflag	char(3)		Low precision indicator (Y=yes, N=no)
f2pct	number(6,2)		More than yearly: percent frequency category rating for each task of O*NET occupation
Nf2	number(4,0)		Sample size
f2stderr	number(6,2)		Standard error
f2lower	number(6,2)		Lower 95% Confidence Interval Bound
f2upper	number(6,2)		Upper 95% Confidence Interval Bound
f2supflag	char(3)		Low precision indicator (Y=yes, N=no)
f3pct	number(6,2)		More than monthly: percent frequency category rating for each task of O*NET occupation
Nf3	number(4,0)		Sample size
f3stderr	number(6,2)		Standard error
f3lower	number(6,2)		Lower 95% Confidence Interval Bound
f3upper	number(6,2)		Upper 95% Confidence Interval Bound
f3supflag	char(3)		Low precision indicator (Y=yes, N=no)
f4pct	number(6,2)		More than weekly: percent frequency category rating for each task of O*NET occupation
Nf4	number(4,0)		Sample size
f4stderr	number(6,2)		Standard error
f4lower	number(6,2)		Lower 95% Confidence Interval Bound
f4upper	number(6,2)		Upper 95% Confidence Interval Bound
f4supflag	char(3)		Low precision indicator (Y=yes, N=no)

f5pct	number(6,2)		Daily : percent frequency category rating for each task of O*NET occupation
Nf5	number(4,0)		Sample size
f5stderr	number(6,2)		Standard error
f5lower	number(6,2)		Lower 95% Confidence Interval Bound
f5upper	number(6,2)		Upper 95% Confidence Interval Bound
f5supflag	char(3)		Low precision indicator (Y=yes, N=no)
f6pct	number(6,2)		Several times daily : percent frequency category rating for each task of O*NET occupation
Nf6	number(4,0)		Sample size
f6stderr	number(6,2)		Standard error
f6lower	number(6,2)		Lower 95% Confidence Interval Bound
f6upper	number(6,2)		Upper 95% Confidence Interval Bound
f6supflag	char(3)		Low precision indicator (Y=yes, N=no)
f2pct	number(6,2)		More than yearly : percent frequency category rating for each task of O*NET occupation
Nf7	number(4,0)		Sample size
f7stderr	number(6,2)		Standard error
f7lower	number(6,2)		Lower 95% Confidence Interval Bound
f7upper	number(6,2)		Upper 95% Confidence Interval Bound
f7supflag	char(3)		Low precision indicator (Y=yes, N=no)
Date	char(7)		Date when data were updated (MM/YYYY)
sourcecode	char(1)	2	Code for source of the data
Constraint Information			
1 Foreign Key references: onetcode.onetcode			
2 Foreign Key references: comsourc.sourcecode			
Other Information			
◆ 16,305 Records			
◆ Source table: tasks			

occmeta – O*NET occupational level metadata associated with the incumbent data collection.			
Column	Type	Constraint	Description
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
Item	char(150)	Primary Key	Occupational-level statistic
Response	char(75)	Primary Key	Response value
N	number(4)		Sample size
Percent	number(6,2)		Percentage
Date	char(7)		Date when data were updated (MM/YYYY)
Constraint Information			
1 Foreign Key references: onetcode.onetcode			
Other Information			
◆ 3,960 Records			
◆ Source table: OccLevelMetadata			

anchors – Descriptions of O*NET level scale anchors.			
Column	Type	Constraint	Description
elementid	char(15)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
scaleid	char(3)	Primary Key 2	Occupational-level statistic
anchorval	number(3)	Primary Key*	Response value
anchordesc	memo		Sample size
Constraint Information			
1 Foreign Key references: contmodel.elementid 2 Foreign Key references: scaleref.scaleid * Primary key uses character equivalent of this variable			
Other Information			
<ul style="list-style-type: none"> ◆ 483 Records ◆ Source table: anchors 			

survbook – Work Styles Descriptors and their ratings for each occupation			
Column	Type	Constraint	Description
Elementid	char(15)	Primary Key 1	Unique code for O*NET Content Model descriptors
survitem	char(4)		Survey booklet location number
Constraint Information			
1 Foreign Key references: contmodel.elementid			
Other Information			
<ul style="list-style-type: none"> ◆ 238 Records ◆ Source table: Survey Booklet Location 			

O*NET 6.0 Data Dictionary – Supplemental Table Formats

Descriptive Tables: These tables contain information describing the classifications and variables found in the O*NET database. (NOTE: These tables were not revised with the release of the O*NET 6.0 database. They are taken directly from the O*NET 4.0 database.)

socode -- This table contains one record for each occupation in the 1998 Standard Occupational Classification			
Column	Type	Constraint	Description
Socode	char(6)	Primary Key	Standard Occupational Classification code
Soctitle	char(105)		SOC Occupation title
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> ◆ 846 Records ◆ O*NET source table: soc_classification 			

dotcode -- This table provides a listing of titles for all DOT codes found in the DOTXONET crosswalk table			
Column	Type	Constraint	Description
dotcode	char(9)	Primary Key	Dictionary of Occupational Titles code
dottitle	char(70)		DOT Occupation title
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> ◆ 12,814 Records ◆ Source table: dot_to_onet_soc_crosswalk 			

oucode -- This table provides a listing of titles for all Occupational Unit (OU) codes from the O*NET 98 classification found in the ONETXOU crosswalk table			
Column	Type	Constraint	Description
oucode	char(6)	Primary Key	Occupational Unit code, from O*NET98
outitle	char(95)		OU Occupation title
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> ◆ 854 Records ◆ Source table: soc_ou_onet_soc_crosswalk 			

raiscode -- This table provides a listing of titles for all Registered Apprenticeship Information System codes.			
Column	Type	Constraint	Description
raiscode	char(4)	Primary Key	RAIS code
raistitle	char(89)		RAIS title
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> ◆ 856 Records ◆ Source table: RAIS-O*NET crosswalk table 			

mocode -- This table provides a listing of titles for all Military Occupations used in O*NET Online			
Column	Type	Constraint	Description
Mocsvc	char(1)	Primary Key	Military service of the occupation (see below)
moceo	char(1)	Primary Key	Officer/enlisted indicator (see below)
Moctype	Char(2)	Primary Key	Military occupation type (see below)
Mocode	Char(10)	Primary Key	Military occupation code
payrange	char(4)	Primary Key	Pay grade range
mocitle	char(185)		Military occupation title
Constraint Information			
N/A			
Other Information			
◆ 5,503 Records			
◆ Source table: moc-onet review.mdb			

variable	Description
Mocsvc	Service Branch: A=Army C=Coast Guard F=Air Force M=Marine Corps N=Navy
Moceo	Military Personnel Category E=Enlisted O=Commissioned or Warrant Officer W=Warrant Officer only
Moctype	MOC Type: AA=Army Commissioned Officer Area of Concentration (AOC) AS=Army Commissioned Officer Skill Code (SI) AJ=Army Warrant Officer Additional Skill Identifier (ASI) AR= Army Warrant Officer Special Qualification Identifier (SQI) AW= Army Warrant Officer Military Occupational Specialty (MOS) AI =Army Enlisted Additional Skill Identifier (ASI) AM= Army Enlisted Military Occupational Specialty (MOS) AQ= Army Enlisted Special Qualification Identifier (SQI) CN=Coast Guard Commissioned Officer Occupational Field (OCC FLD) CW=Coast Guard Warrant Officer Specialty CR=Coast Guard Enlisted Rating FA=Air Force Specialty Code (AFSC) Commissioned Officer FA=Air Force Specialty Code (AFSC) Enlisted MM=Marine Corps Commissioned Officer Military Occupational Specialty (MOS) MM=Marine Corps Warrant Officer MOS MM=Marine Corps Enlisted MOS NB=Navy Officer Billet Code (NOBC) NR=Navy Enlisted Rating NE=Navy Enlisted Classification (NEC)
Mocode	Military Occupational Code
Mocitle	Military Occupational Title
Payrange	Pay Grade Range

Crosswalk tables: These tables incorporate the relationships among the various classifications found in the O*NET database. (NOTE: These tables were not revised with the release of the O*NET 56.0 database. They are taken directly from the O*NET 4.0 database.)

reloccs -- Occupations related to each O*NET-SOC occupation			
Column	Type	Constraint	Description
Onetcode	Char(8)	Primary Key 1	Unique ONET-SOC Code
Relonetcd	Char(8)	Primary Key 2	Unique ONET-SOC Code of related occupation
Constraint Information			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: onetcode.onetcode			
Other Information			
<ul style="list-style-type: none"> ◆ 6,397 Records ◆ Source table: related_occupation_data (replaced 15301100 with 152091) 			

onetxsoc -- Crosswalk between the O*NET-SOC occupations and the SOC.			
Column	Type	Constraint	Description
onetcode	char(8)	Primary Key 1	Unique ONET-SOC Code
soccode	char(6)	Primary Key 2	Unique SOC Code
Constraint Information			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: onetcode.onetcode			
Other Information			
<ul style="list-style-type: none"> ◆ 1,166 Records ◆ Source table: soc_ou_onetsoc_crosswalk 			

onetxou -- Crosswalk between the O*NET-SOC occupations and the O*NET98 occupation unit codes.			
Column	Type	Constraint	Description
onetcode	char(8)	Primary Key 1	Unique ONET-SOC Code
oucode	char(6)	Primary Key	Unique SOC Code
Constraint Information			
1 Foreign Key references: onetcode.onetcode			
Other Information			
<ul style="list-style-type: none"> ◆ 900 Records ◆ Source table: soc_ou_onetsoc_crosswalk 			

dotxonet -- Crosswalk between DOT and O*NET-SOC codes (has 12,814 DOT occupations)			
Column	Type	Constraint	Description
dotcode	char(9)	Primary Key 1	Dictionary of Occupation Titles' Code
onetcode	char(8)	Primary Key 2	Unique ONET-SOC Code
Constraint Information			
1 Foreign Key references: dotcode.dotcode 2 Foreign Key references: onetcode.onetcode			
Other Information			
<ul style="list-style-type: none"> ◆ 12,945 Records ◆ Source table: dot_to_onetsoc_crosswalk 			

mocxonet – Crosswalk between O*NET-SOC and military occupations			
Column	Type	Constraint	Description
Onetcode	Char(8)	Primary Key 1	Unique O*NET-SOC Code
Mocsvc	char(1)	Primary Key 2	Military service of the occupation (see below)
moceo	char(1)	Primary Key 2	Officer/enlisted indicator (see below)
Moctype	Char(2)	Primary Key 2	Military occupation type (see below)
payrange	char(4)	Primary Key 2	Pay grade range
Moccode	Char(10)	Primary Key 2	Military occupation code
Constraint Information			
1 Foreign Key references: onetcode.onetcode			
2 Foreign Key references: moccode.mocsvc,moccode.mocsvc, moccode.moceo, moccode.moctype, moccode.payrange, moccode.moccode			
Other Information			
◆ 5,503 Records			
◆ Source table: moc-onet review.mdb			

raisonet – Crosswalk between O*NET-SOC and Registered Apprenticeship Information System codes.			
Column	Type	Constraint	Description
raiscode	char(4)	Primary Key 1	RAIS code
onetcode	char(8)	Primary Key 2	Unique O*NET-SOC Code
Constraint Information			
1 Foreign Key references: onetcode.onetcode			
2 Foreign Key references: raiscode.raiscode			
Other Information			
◆ 856 Records			
◆ Source table: RAIS-O*NET crosswalk table			