

O\*NET 9.0 Development Database  
Data Dictionary  
Visual FoxPro Version



ALMIS Resource Center  
<http://www.almisdb.org/>

and

National Crosswalk Service Center  
Department of Education  
Grimes State Office Building  
Des Moines, Iowa 50319

<http://www.xwalkcenter.org/onet80/index.html>

Telephone 515-242-5034

# Data Dictionary

## O\*NET 8.0 Database

### Visual FoxPro Version

#### Introduction

O\*NET, the Occupational Information Network, is a comprehensive database of worker attributes and job characteristics. As the replacement for the Dictionary of Occupational Titles (DOT), O\*NET is the nation's primary source of occupational information.

Information from the O\*NET Database is available from the National O\*NET Consortium (<http://www.onetcenter.org/>). The consortium utilizes two means of delivery: an on-line database viewer (<http://online.onetcenter.org/>) and a downloadable database consisting of a series of tab-delimited text files, along with related file documentation ([http://www.onetcenter.org/dev\\_db.html](http://www.onetcenter.org/dev_db.html)).

The National Crosswalk Service Center (NCSC) has distributed resources related to occupational classifications such as the DOT and O\*NET since 1983. The contents of the files described in this document were taken from the database downloaded from the third Internet page cited above. The tables are also available in a tab-delimited text, MS Access and SAS/PC formats. This document describes the format of the Visual FoxPro database. File layouts for the other versions differ. Contact the NCSC for more information.

The contents of the files in the database described in this document were adapted from the files downloaded from the consortium web site. Some fields were eliminated from these tables to eliminate redundancy and bring the database into a more normalized configuration. The development of the structure was a joint venture by the NCSC and the ALMIS Resource Center. The structure contains variable names and formats and uses naming conventions that are consistent with the ALMIS Database.

#### Database Changes

The O\*NET 9.0 database is the fifth to include new data from the O\*NET Data Collection Program and brings to 480 the number of occupations with information collected through that program. For a brief history of O\*NET database revisions, visit [http://www.onetcenter.org/dev\\_db.html#updates](http://www.onetcenter.org/dev_db.html#updates)

What's new in Version 9.0:

- Addition of Task Statement ratings (importance, relevance, and frequency) for 100 O\*NET-SOC occupations
- Updated Abilities, Work Activities, Knowledge, Skills, and Work Context data for 100 occupations
- Additional Work Context data for 100 occupations
- Addition Training and Work Experience and Education data for 100 occupations
- Addition of Work Styles data for 100 occupations

With the introduction of information from the data collection program in version 5.0 of the database, the O\*NET database no longer contains a homogeneous set of variables and measures for all occupations. The O\*NET Center continues to make version 4.0 of the database available on their web site. That is the last version made up entirely of analyst data, with a uniform set of descriptors. The NCSC continues to make the Visual FoxPro, SAS/PC and MS Access versions available at <http://www.xwalkcenter.org/onet40/index.html>.

## HOW TO READ A TABLE DEFINITION

Each table definition contains complete information about the structure of a table. Each definition includes: the name of the table, a complete list of each column name and data type, complete constraint information, and short descriptions of the columns. The following illustration identifies each component of a table definition.

**Interest** -- Interest Descriptors and their ratings for each occupation

Column	Type	Constraint	Description
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
Scalid	char(2)	Primary Key 3	Unique code for O*NET descriptors scale
datavalue	number(6,2)		Value of descriptor rating
<b>Constraint Information</b>			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid			
<b>Other Information</b>			
◆ 8,100 Records ◆ Source table: interest			

**Constraint:** Specifies whether this column is part of the Primary Key or participates in one or more Foreign Keys. Numbers in this column refer to Foreign Keys where more detailed information can be found in the **Constraints Information** section.

**Other Information:** Provides count of the number of records in the table and the table(s) in the source O\*NET database from which the contents were derived.

**Constraint Information:** Provides complete information on each Foreign Key used in the table. Each note indicates which table and columns are being referenced.

Short description of the data intended for this column.

## TABLE CONSTRAINTS

The Constraint section of each table definition identifies all Primary Keys and Foreign Keys for the table. The constraints for a table specify rules for data that will be stored in that table. These rules exist in the form of either Primary Keys or Foreign Keys. The definitions of these terms appear below:

**Primary Key:** The *Primary Key* is a column or group of columns that shall always be (1) non-null and (2) unique. Only one primary key exists for each table. A Primary Key constraint is enforced on a table so that each row in the table can be uniquely identified.

**Foreign Key:** A *Foreign Key* is a column or group of columns where each value or group of values exists as a Primary Key in another table. Foreign Key constraints are used so that data for a column or group of columns can be validated against another table containing a list of valid values for that column or group of columns.

## O\*NET 9.0 Data Dictionary – Core Table Formats

**Descriptive Tables:** These tables contain information describing the classifications and variables found in the O\*NET 9.0 database.

<b>onetcode</b> -- This table contains one record for each O*NET Occupation			
Column	Type	Constraint	Description
onetcode	char(8)	Primary Key	Unique occupation code based on SOC code, modified for O*NET
onetttitle	char(105)		Occupation title
onetdesc	memo		Description of occupation
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> <li>◆ 1,167 Records</li> <li>◆ O*NET source tables: Occupation Data</li> </ul>			

<b>contmodl</b> -- O*NET content model reference			
Column	Type	Constraint	Description
elementid	char(15)	Primary Key	Unique code for ratings Scale
elemntname	char(140)		Descriptor Name
elemntdesc	memo		Description of Descriptor
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> <li>◆ 564 Records</li> <li>◆ Source table: Content Model Reference</li> </ul>			

<b>scaleref</b> – Provides a reference to the scale names and values			
Column	Type	Constraint	Description
scaleid	char(3)	Primary Key	Unique code for ratings Scale
scalename	char(50)		Name of Scale
scalemmin	Number(3,0)		Minimum value the descriptor scale can take
scalemmax	Number(3,0)		Maximum value the descriptor scale can take
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> <li>◆ 69 Records</li> <li>◆ Source table: Scales Reference</li> </ul>			

<b>jobzone</b> -- This table contains descriptions of each of O*NET's job zones			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
jobzonecd	char(1)	Primary Key	Unique code for Job Zone
jobzone	char(50)		Name of Job Zone
experience	Memo		Experience required to be considered part of this job zone
education	Memo		Education required to be considered part of this job zone
training	Memo		Training required to be considered part of this job zone
examples	Memo		Examples of the types of jobs in this job zone
svprange	char(15)		
<b>Constraint Information</b>			
N/A			
<b>Other Information</b>			
<ul style="list-style-type: none"> <li>◆ 5 Records</li> <li>◆ Source table: Job Zone Reference</li> </ul>			

<b>contxcat</b> – Descriptions of Work Context categories.			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
elementid	char(15)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
ecaleid	char(3)	Primary Key 2	Occupational-level statistic
category	char(1)	Primary Key	Category value associated with element
catdesc	Memo		Detail description of category associated with element
<b>Constraint Information</b>			
1 Foreign Key references: contmodel.elementid 2 Foreign Key references: scaleref.scaleid			
<b>Other Information</b>			
<ul style="list-style-type: none"> <li>◆ 395 Records</li> <li>◆ Source table: Work Context Categories (<b>new in version 9.0—additional records added by the NCSC for null values in category (replaced nulls with zeros)</b>)</li> </ul>			

<b>edcat</b> – Descriptions of the Education, Training and Experience percent frequency categories.			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
elementid	char(15)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
scaleid	char(3)	Primary Key 2	Occupational-level statistic
category	char(2)	Primary Key	Category value associated with element
catdesc	Memo		Detail description of category associated with element
<b>Constraint Information</b>			
1 Foreign Key references: contmodel.elementid 2 Foreign Key references: scaleref.scaleid			
<b>Other Information</b>			
<ul style="list-style-type: none"> <li>◆ 41 Records</li> <li>◆ Source table: Education Training and Experience Categories (<b>new in version 9.0</b>)</li> </ul>			

<b>domsourc</b> -- This table contains one record for data source			
Column	Type	Constraint	Description
sourccode	char(1)	Primary Key	Unique code for each source
domsourc	char(30)		Source description
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> <li>◆ 4 Records</li> <li>◆ O*NET source tables: None (created by NCSC)</li> </ul>			

**Data tables:** These tables contain the variables which define the characteristics of O\*NET occupations.

<b>ability -- Ability Descriptors and their ratings for each occupation</b>			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	char(3)	Primary Key 3	Unique code for O*NET descriptors scale
datavalue	number(6,2)		Value of descriptor rating
n	number(4)		Sample size
stderr	number(6,2)		Standard error
lowerci	number(6,2)		Lower 95% confidence interval bound
upperci	number(6,2)		Upper 95% confidence interval bound
supflag	char(3)		Suppression recommended (low precision indicator – Y=Yes, N=No)
notrel	char(3)		Not relevant for the occupation (Y=Yes, N=No)
date	char(7)		Date when data were updated (MM/YYYY)
sourccode	char(1)	4	Code for source of the data
<b>Constraint Information</b>			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid 4 Foreign Key references: comsourc.sourccode			
<b>Other Information</b>			
◆ 97,864 Records ◆ Source table: Abilities			

<b>educ – Mapping of O*NET codes to education, training and experience ratings</b>			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	char(3)	Primary Key 3	Unique code for O*NET descriptors scale
category	char(2)	Primary Key	Percent frequency category (refer to bookloc table)
datavalue	number(6,2)		Value of descriptor rating
n	number(4)		Sample size
stderr	number(6,2)		Standard error
lowerci	number(6,2)		Lower 95% confidence interval bound
upperci	number(6,2)		Upper 95% confidence interval bound
supflag	char(3)		Suppression recommended (low precision indicator – Y=Yes, N=No)
date	char(7)		Date when data were updated (MM/YYYY)
sourccode	char(1)	4	Code for source of the data
<b>Constraint Information</b>			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid 4 Foreign Key references: comsourc.sourccode			
<b>Other Information</b>			
◆ 19,680 Records ◆ Source table: Education Training and Experience			

<b>interest</b> – Interest Descriptors and their ratings for each occupation			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	char(3)	Primary Key 3	Unique code for O*NET descriptors scale
datavalue	number(6,2)		Value of descriptor rating
date	char(7)		Date when data were updated (MM/YYYY)
sourccode	char(1)	4	Code for source of the data
<b>Constraint Information</b>			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid 4 Foreign Key references: comsourc.sourccode			
<b>Other Information</b>			
◆ 8,100 Records ◆ Source table: Interests			

<b>knowledg</b> – Knowledge Descriptors and their ratings for each occupation			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	char(3)	Primary Key 3	Unique code for O*NET descriptors scale
datavalue	number(6,2)		Value of descriptor rating
n	number(4)		Sample size
stderr	number(6,2)		Standard error
lowerci	number(6,2)		Lower 95% confidence interval bound
upperci	number(6,2)		Upper 95% confidence interval bound
supflag	char(3)		Suppression recommended (low precision indicator – Y=Yes, N=No)
notrel	char(3)		Not relevant for the occupation (Y=Yes, N=No)
sate	char(7)		Date when data were updated (MM/YYYY)
sourccode	char(1)	4	Code for source of the data
<b>Constraint Information</b>			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid 4 Foreign Key references: comsourc.sourccode			
<b>Other Information</b>			
◆ 62,106 Records ◆ Source table: Knowledge			

<b>onetzone</b> -- This table contains the Job Zone value for each O*NET-SOC Occupation			
Column	Type	Constraint	Description
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
jobzonecd	char(1)	2	Job Zone of the O*NET-SOC occupation
date	char(7)		Date when data were updated (MM/YYYY)
sourccode	char(1)	3	Code for source of the data
Constraint Information			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: jobzone.jobzonecd 3 Foreign Key references: comsourc.sourccode			
Other Information			
◆ 941 Records ◆ O*NET source tables: Job Zones			

<b>skills</b> -- Skills Descriptors and their ratings for each occupation			
Column	Type	Constraint	Description
onetcode	Char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	Char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	Char(3)	Primary Key 3	Unique code for O*NET descriptors scale
datavalue	number(6,2)		Value of descriptor rating
n	number(4)		Sample size
stderr	number(6,2)		Standard error
lowerci	number(6,2)		Lower 95% confidence interval bound
upperci	number(6,2)		Upper 95% confidence interval bound
supflag	Char(3)		Suppression recommended (low precision indicator – Y=Yes, N=No)
notrel	Char(3)		Not relevant for the occupation (Y=Yes, N=No)
date	Char(7)		Date when data were updated (MM/YYYY)
sourccode	Char(1)	4	Code for source of the data
Constraint Information			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid 4 Foreign Key references: comsourc.sourccode			
Other Information			
◆ 65,870 Records ◆ Source table: Skills			

<b>activity -- Work Activity Descriptors and their ratings for each occupation</b>			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	char(3)	Primary Key 3	Unique code for O*NET descriptors scale
datavalue	number(6,2)		Value of descriptor rating
n	number(4)		Sample size
stderr	number(6,2)		Standard error
lowerci	number(6,2)		Lower 95% confidence interval bound
upperci	number(6,2)		Upper 95% confidence interval bound
supflag	char(3)		Suppression recommended (low precision indicator – Y=Yes, N=No)
notrel	char(3)		Not relevant for the occupation (Y=Yes, N=No)
date	char(7)		Date when data were updated (MM/YYYY)
sourccode	char(1)	4	Code for source of the data
<b>Constraint Information</b>			
1 Foreign Key references: onetcode.onetcode			
2 Foreign Key references: contmodel.elementid			
3 Foreign Key references: scaleref.scaleid			
4 Foreign Key references: comsourc.sourccode			
<b>Other Information</b>			
◆ 77,162 Records			
◆ Source table: Work Activities			

<b>context -- Work Context Descriptors and their ratings for each occupation</b>			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	char(3)	Primary Key 3	Unique code for O*NET descriptors scale
category	char(1)	Primary Key	Percent frequency category (refer to bookloc table)
datavalue	number(6,2)		Value of descriptor rating
n	number(4)		Sample size
stderr	number(6,2)		Standard error
lowerci	number(6,2)		Lower 95% confidence interval bound
upperci	number(6,2)		Upper 95% confidence interval bound
supflag	char(3)		Suppression recommended (low precision indicator – Y=Yes, N=No)
notrel	char(3)		Not relevant for the occupation (Y=Yes, N=No)
date	char(7)		Date when data were updated (MM/YYYY)
sourccode	char(1)	4	Code for source of the data
<b>Constraint Information</b>			
1 Foreign Key references: onetcode.onetcode			
2 Foreign Key references: contmodel.elementid			
3 Foreign Key references: scaleref.scaleid			
4 Foreign Key references: comsourc.sourccode			
<b>Other Information</b>			
◆ 179,758 Records			
◆ Source table: Work Context			

<b>styles -- Work Styles Descriptors and their ratings for each occupation</b>			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	char(3)	Primary Key 3	Unique code for O*NET descriptors scale
datavalue	number(6,2)		Value of descriptor rating
n	number(4)		Sample size
stderr	number(6,2)		Standard error
lowerci	number(6,2)		Lower 95% confidence interval bound
upperci	number(6,2)		Upper 95% confidence interval bound
supflag	char(3)		Suppression recommended (low precision indicator – Y=Yes, N=No)
date	char(7)		Date when data were updated (MM/YYYY)
sourccode	char(1)	4	Code for source of the data
<b>Constraint Information</b>			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid 4 Foreign Key references: comsourc.sourccode			
<b>Other Information</b>			
◆ 7,680 Records ◆ Source table: Work Styles			

<b>workvalu -- Work Value Descriptors and their ratings for each occupation</b>			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
elementid	char(15)	Primary Key 2	Unique code for O*NET Content Model descriptors
scaleid	char(3)	Primary Key 3	Unique code for O*NET descriptors scale
datavalue	number(6,2)		Value of descriptor rating
date	char(7)		Date when data were updated (MM/YYYY)
sourccode	char(1)	4	Code for source of the data
<b>Constraint Information</b>			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: contmodel.elementid 3 Foreign Key references: scaleref.scaleid 4 Foreign Key references: comsourc.sourccode			
<b>Other Information</b>			
◆ 24,300 Records ◆ Source table: Work Values			

<b>tasks --</b> Provides each O*NET-SOC code (occupation) mapping to several tasks associated with the occupation <b>NOTE:</b> This table did not have a unique field as received from O*NET. The table was restructured to include a unique Primary Key by the addition of the Task Number field.			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
onetcode	char(8)	Primary Key 1	Unique ONET-SOC Code
tasknumber	char(3)	Primary Key	Line number of each task within ONET-SOC Code
taskid	number(8,0)		Identifies each task containing data ratings
task	Memo		Tasks involved in occupation
tasktype	char(12)		Core or supplemental
incumb	number(4,0)		Number of incumbents providing task information
scaleid	char(3)		Scale used as the basis for the rating
datavalue	number(6,2)		Rating associated with each task of O*NET occupation
n	number(4,0)		Sample size
stderr	number(6,2)		Standard error
lowerci	number(6,2)		Lower 95% Confidence Interval Bound
upperci	number(6,2)		Upper 95% Confidence Interval Bound
supflag	char(3)		Low precision indicator (Y=yes, N=no)
pctrel	number(6,2)		Relevance of each task to the O*NET occupation
nr	number(4,0)		Sample size
rstder	number(6,2)		Standard error
rlower	number(6,2)		Lower 95% Confidence Interval Bound
rupper	number(6,2)		Upper 95% Confidence Interval Bound
rsupflag	char(3)		Low precision indicator (Y=yes, N=no)
f1pct	number(6,2)		<b>Yearly or less:</b> percent frequency category rating for each task of O*NET occupation
nf1	number(4,0)		Sample size
f1stderr	number(6,2)		Standard error
f1lower	number(6,2)		Lower 95% Confidence Interval Bound
f1upper	number(6,2)		Upper 95% Confidence Interval Bound
f1supflag	char(3)		Low precision indicator (Y=yes, N=no)
f2pct	number(6,2)		<b>More than yearly:</b> percent frequency category rating for each task of O*NET occupation
nf2	number(4,0)		Sample size
f2stderr	number(6,2)		Standard error
f2lower	number(6,2)		Lower 95% Confidence Interval Bound
f2upper	number(6,2)		Upper 95% Confidence Interval Bound
f2supflag	char(3)		Low precision indicator (Y=yes, N=no)
f3pct	number(6,2)		<b>More than monthly:</b> percent frequency category rating for each task of O*NET occupation
nf3	number(4,0)		Sample size
f3stderr	number(6,2)		Standard error
f3lower	number(6,2)		Lower 95% Confidence Interval Bound
f3upper	number(6,2)		Upper 95% Confidence Interval Bound
f3supflag	char(3)		Low precision indicator (Y=yes, N=no)
f4pct	number(6,2)		<b>More than weekly:</b> percent frequency category rating for each task of O*NET occupation
nf4	number(4,0)		Sample size
f4stderr	number(6,2)		Standard error
f4lower	number(6,2)		Lower 95% Confidence Interval Bound
f4upper	number(6,2)		Upper 95% Confidence Interval Bound
f4supflag	char(3)		Low precision indicator (Y=yes, N=no)

f5pct	number(6,2)		<b>Daily:</b> percent frequency category rating for each task of O*NET occupation
nf5	number(4,0)		Sample size
f5stderr	number(6,2)		Standard error
f5lower	number(6,2)		Lower 95% Confidence Interval Bound
f5upper	number(6,2)		Upper 95% Confidence Interval Bound
f5supflag	char(3)		Low precision indicator (Y=yes, N=no)
f6pct	number(6,2)		<b>Several times daily:</b> percent frequency category rating for each task of O*NET occupation
nf6	number(4,0)		Sample size
f6stderr	number(6,2)		Standard error
f6lower	number(6,2)		Lower 95% Confidence Interval Bound
f6upper	number(6,2)		Upper 95% Confidence Interval Bound
f6supflag	char(3)		Low precision indicator (Y=yes, N=no)
f7pct	number(6,2)		<b>More than yearly:</b> percent frequency category rating for each task of O*NET occupation
nf7	number(4,0)		Sample size
f7stderr	number(6,2)		Standard error
f7lower	number(6,2)		Lower 95% Confidence Interval Bound
f7upper	number(6,2)		Upper 95% Confidence Interval Bound
f7supflag	char(3)		Low precision indicator (Y=yes, N=no)
date	char(7)		Date when data were updated (MM/YYYY)
sourccode	char(1)	2	Code for source of the data
<b>Constraint Information</b>			
1 Foreign Key references: onetcode.onetcode			
2 Foreign Key references: comsourc.sourccode			
<b>Other Information</b>			
◆ 16,805 Records			
◆ Source table: Tasks			

<b>occmeta</b> – O*NET occupational level metadata associated with the incumbent data collection.			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
onetcode	char(8)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
item	char(150)	Primary Key	Occupational-level statistic
response	char(75)	Primary Key	Response value
n	number(4)		Sample size
percent	number(6,2)		Percentage
date	char(7)		Date when data were updated (MM/YYYY)
<b>Constraint Information</b>			
1 Foreign Key references: onetcode.onetcode			
<b>Other Information</b>			
◆ 10,560 Records			
◆ Source table: Occupation Level Metadata			

<b>anchors</b> – Descriptions of O*NET level scale anchors.			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
elementid	char(15)	Primary Key 1	Unique occupation code based on SOC code, modified for O*NET
scaleid	char(3)	Primary Key 2	Occupational-level statistic
anchorval	number(3)	Primary Key*	Response value
anchordesc	Memo		Sample size
<b>Constraint Information</b>			
1 Foreign Key references: contmodel.elementid 2 Foreign Key references: scaleref.scaleid * Primary key uses character equivalent of this variable			
<b>Other Information</b>			
<ul style="list-style-type: none"> <li>◆ 483 Records</li> <li>◆ Source table: Level Scale Anchors</li> </ul>			

<b>survbook</b> – Work Styles Descriptors and their ratings for each occupation			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
elementid	char(15)	Primary Key 1	Unique code for O*NET Content Model descriptors
survitem	char(4)		Survey booklet location number
<b>Constraint Information</b>			
1 Foreign Key references: contmodel.elementid			
<b>Other Information</b>			
<ul style="list-style-type: none"> <li>◆ 238 Records</li> <li>◆ Source table: Survey Booklet Locations</li> </ul>			

## O\*NET 8.0 Data Dictionary – Supplemental Table Formats

**Descriptive Tables:** These tables contain information describing the classifications and variables found in the O\*NET database. (NOTE: Some tables were revised at about the time of the release of the O\*NET 8.0 database. Those are identified in the “O\*NET source table” section for each table. The others are taken directly from the O\*NET 4.0 database.)

<b>socode</b> -- This table contains one record for each occupation in the 1998 Standard Occupational Classification			
Column	Type	Constraint	Description
socode	char(6)	Primary Key	Standard Occupational Classification code
soctitle	char(105)		SOC Occupation title
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> <li>◆ 846 Records</li> <li>◆ O*NET source table: soc_classification</li> </ul>			

<b>dotcode</b> -- This table provides a listing of titles for all DOT codes found in the DOTXONET crosswalk table			
Column	Type	Constraint	Description
dotcode	char(9)	Primary Key	Dictionary of Occupational Titles code
dottitle	char(70)		DOT Occupation title
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> <li>◆ 12,814 Records</li> <li>◆ Source table: dot_to_onetsoc_crosswalk</li> </ul>			

<b>oucode</b> -- This table provides a listing of titles for all Occupational Unit (OU) codes from the O*NET 98 classification found in the ONETXOU crosswalk table			
Column	Type	Constraint	Description
oucode	char(6)	Primary Key	Occupational Unit code, from O*NET98
outitle	char(95)		OU Occupation title
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> <li>◆ 854 Records</li> <li>◆ Source table: soc_ou_onetsoc_crosswalk</li> </ul>			

<b>raiscode</b> -- This table provides a listing of titles for all Registered Apprenticeship Information System codes.			
Column	Type	Constraint	Description
raiscode	char(4)	Primary Key	RAIS code
raistitle	char(89)		RAIS title
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> <li>◆ 874 Records</li> <li>◆ Source table: RAIS-O*NET crosswalk table (<b>revised in Version 8.0</b>)</li> </ul>			

<b>moccode</b> -- This table provides a listing of titles for all Military Occupations used in O*NET Online			
Column	Type	Constraint	Description
mocsvc	char(1)	Primary Key	Military service of the occupation (see below)
moceo	char(1)	Primary Key	Officer/enlisted indicator (see below)
moccode	Char(10)	Primary Key	Military occupation code
moctitle	char(185)		Military occupation title
Constraint Information			
N/A			
Other Information			
<ul style="list-style-type: none"> <li>◆ 17,242 Records</li> <li>◆ Source table: crosswalks 0205.mdb (<b>revised in Version 8.0</b>)</li> </ul>			

variable	Description
mocsvc	Service Branch: A=Army C=Coast Guard F=Air Force M=Marine Corps N=Navy
moceo	Military Personnel Category E=Enlisted O=Commissioned or Warrant Officer W=Warrant Officer only

**Crosswalk tables:** These tables incorporate the relationships among the various classifications found in the O\*NET database. (NOTE: These tables were not revised with the release of the O\*NET 7.0 database. They are taken directly from the O\*NET 4.0 database.)

<b>reloccs -- Occupations related to each O*NET-SOC occupation</b>			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
onetcode	Char(8)	Primary Key 1	Unique ONET-SOC Code
relonetcd	Char(8)	Primary Key 2	Unique ONET-SOC Code of related occupation
<b>Constraint Information</b>			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: onetcode.onetcode			
<b>Other Information</b>			
<ul style="list-style-type: none"> <li>◆ 6,397 Records</li> <li>◆ Source table: related_occupation_data (replaced 15301100 with 152091)</li> </ul>			

<b>onetxsoc -- Crosswalk between the O*NET-SOC occupations and the SOC.</b>			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
onetcode	char(8)	Primary Key 1	Unique ONET-SOC Code
soccode	char(6)	Primary Key 2	Unique SOC Code
<b>Constraint Information</b>			
1 Foreign Key references: onetcode.onetcode 2 Foreign Key references: onetcode.onetcode			
<b>Other Information</b>			
<ul style="list-style-type: none"> <li>◆ 1,166 Records</li> <li>◆ Source table: soc_ou_onetsoc_crosswalk</li> </ul>			

<b>onetxou -- Crosswalk between the O*NET-SOC occupations and the O*NET98 occupation unit codes.</b>			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
onetcode	char(8)	Primary Key 1	Unique ONET-SOC Code
oucode	char(6)	Primary Key	Unique SOC Code
<b>Constraint Information</b>			
1 Foreign Key references: onetcode.onetcode			
<b>Other Information</b>			
<ul style="list-style-type: none"> <li>◆ 900 Records</li> <li>◆ Source table: soc_ou_onetsoc_crosswalk</li> </ul>			

<b>dotxonet -- Crosswalk between DOT and O*NET-SOC codes (has 12,814 DOT occupations)</b>			
<b>Column</b>	<b>Type</b>	<b>Constraint</b>	<b>Description</b>
dotcode	char(9)	Primary Key 1	Dictionary of Occupation Titles' Code
onetcode	char(8)	Primary Key 2	Unique ONET-SOC Code
<b>Constraint Information</b>			
1 Foreign Key references: dotcode.dotcode 2 Foreign Key references: onetcode.onetcode			
<b>Other Information</b>			
<ul style="list-style-type: none"> <li>◆ 12,945 Records</li> <li>◆ Source table: dot_to_onetsoc_crosswalk</li> </ul>			

<b>mocxonet</b> – Crosswalk between O*NET-SOC and military occupations			
Column	Type	Constraint	Description
onetcode	Char(8)	Primary Key 1	Unique O*NET-SOC Code
mocsvc	char(1)	Primary Key 2	Military service of the occupation (see below)
moceo	char(1)	Primary Key 2	Officer/enlisted indicator (see below)
moccode	Char(10)	Primary Key 2	Military occupation code
Constraint Information			
1 Foreign Key references: onetcode.onetcode			
2 Foreign Key references: moccode.mocsvc, moccode.moceo, moccode.moccode			
Other Information			
◆ 9,084 Records			
◆ Source table: crosswalks 0205.mdb			

<b>raisonet</b> – Crosswalk between O*NET-SOC and Registered Apprenticeship Information System codes.			
Column	Type	Constraint	Description
raiscode	char(4)	Primary Key 1	RAIS code
onetcode	char(8)	Primary Key 2	Unique O*NET-SOC Code
Constraint Information			
1 Foreign Key references: onetcode.onetcode			
2 Foreign Key references: raiscode.raiscode			
Other Information			
◆ 873 Records			
◆ Source table: RAIS-O*NET crosswalk table			